

|                                |                |                 |               |
|--------------------------------|----------------|-----------------|---------------|
| Grind Number:                  | SMC2336AL      |                 |               |
| Lobe Separation:               | 107°           |                 |               |
| Installed Centerline:          | 102°           |                 |               |
|                                | <u>Intake</u>  | <u>Exhaust</u>  |               |
| Lobe Lift:                     | .337"          | .343"           |               |
| Valve Lift w/ 1.5 Ratio:       | .506"          | .515"           |               |
| Valve Lift w/ 1.6 Ratio:       | .539"          | .549"           |               |
| Standard Lifter Pre-Load       | .080"-.095"    |                 |               |
| Duration @ .050"               | 223°           | 236°            |               |
| Cam Timing @ .050" Tappet Lift |                |                 |               |
|                                | <u>Intake</u>  | <u>Exhaust</u>  |               |
| Opens:                         | 10° <b>BTC</b> | 51° <b>BBC</b>  |               |
| Closes:                        | 33° <b>ABC</b> | 6° <b>ATC</b>   |               |
| Valve Spring Requirements      |                |                 |               |
| Rocker Ratio                   | Spring P/N     | Closed Pressure | Open Pressure |
| 1.5                            | 1110           | 120#@1.660"     | 300#@1.160"   |
| 1.6                            | 1110           | 120#@1.660"     | 300#@1.160"   |



Ph:(309)745-9558  
 Fax:(309)296-9990